

LED SELECTION FOR DELIVERY WITHIN 72H



TEC-MAR®

LIGHTING



MICRO 2

mod. PR



Code	W tot.	Mod.	Optic	°K - CRI	LUMEN OUTPUT
7025PR4030BL	30	PR	Symmetric	4000K - CRI>80	3330 Lm

LED | CE | 220 V_~ 240 | -25°C +45°C | IP66 | IK08 | RG0 | CRI >80 | 3 step MacAdam

<10% LOW flicker | L80-B20 >50.000h | ● WHITE | 7 YEARS WARRENTY

POLAR 1

mod. PR

mod. AR



Code	W tot.	Mod.	Optic	°K - CRI	LUMEN OUTPUT
7026PR4040GL	40	PR	Symmetric	4000K - CRI>80	5424 Lm
7026PR4068GL	68	PR	Symmetric	4000K - CRI>80	8017 Lm
7026AR4040GL	40	AR	Asymmetric	4000K - CRI>80	5111 Lm
7026AR4068GL	68	AR	Asymmetric	4000K - CRI>80	7555 Lm

LED | CE | 220 V_~ 240 | -25°C +45°C | IP66 | IK08 | RG0 | CRI >80 CRI >90 | 3 step MacAdam

<7% LOW flicker | L80-B20 >50.000h | L80-B50 >75.000h | 10 kV | ● RAL 9006 | 7 YEARS WARRENTY

POLAR 2

mod. PR

mod. AR



Code	W tot.	Mod.	Optic	°K - CRI	LUMEN OUTPUT
7027PR4080GL	80	PR	Symmetric	4000K - CRI>80	10848 Lm
7027PR4120GL	120	PR	Symmetric	4000K - CRI>80	14985 Lm
7027AR4080GL	80	AR	Asymmetric	4000K - CRI>80	10222 Lm
7027AR4120GL	120	AR	Asymmetric	4000K - CRI>80	14120 Lm

LED | CE | 220 V_~ 240 | -25°C +45°C | IP66 | IK08 | RG0 | CRI >80 CRI >90 | 3 step MacAdam

<7% LOW flicker | L80-B20 >50.000h | L80-B50 >75.000h | 10 kV | ● RAL 9006 | 7 YEARS WARRENTY

POLAR 3

mod. PR

mod. AR



Codice	W tot.	Mod.	Optic	°K - CRI	LUMEN OUTPUT
7028PR4190GL	190	PR	Symmetric	4000K - CRI>80	23646 Lm
7028AR4190GL	190	AR	Asymmetric	4000K - CRI>80	22282 Lm

LED | CE | 220 V_~ 240 | -25°C +45°C | IP66 | IK08 | RG0 | CRI >80 CRI >90 | 3 step MacAdam

<7% LOW flicker | L80-B20 >50.000h | L80-B50 >75.000h | 10 kV | ● RAL 9006 | 7 YEARS WARRENTY

POLAR 4

mod. PR

mod. AR



Code	W tot.	Mod.	Optic	°K - CRI	LUMEN OUTPUT
7029PR4240GL	240	PR	Symmetric	4000K - CRI>80	33236 Lm
7029AR4240GL	240	AR	Asymmetric	4000K - CRI>80	31318 Lm

LED | CE | 220 V_~ 240 | -25°C +45°C | IP66 | IK08 | RG0 | CRI >80 CRI >90 | 3 step MacAdam

<7% LOW flicker | L80-B20 >50.000h | L80-B50 >75.000h | 10 kV | ● RAL 9006 | 7 YEARS WARRENTY

PIER HP

mod. S5



Code	W tot.	Mod.	Optic	°K - CRI	LUMEN OUTPUT
8401S54130GL	130	S5	UGR <25	4000K - CRI>80	19546 Lm
8401S54190GL	190	S5	UGR <25	4000K - CRI>80	26935 Lm

LED | CE | 220 V_~ 240 | -25°C +45°C | IP66 | IK08 | RG0 | CRI >80 CRI >90 | 3 step MacAdam

<7% LOW flicker | L80-B20 >50.000h | L80-B50 >75.000h | 10 kV | ● RAL 9006 | 7 YEARS WARRENTY

LED SELECTION FOR DELIVERY WITHIN 72H



TEC-MAR®

LIGHTING



EVA

mod. LD



Code	W tot.	Mod.	L (mm)	°K - CRI	LUMEN OUTPUT
2100LD4036EL	36	LD	1155 mm	4000K - CRI>80	4392 Lm
2100LD4054EL	54	LD	1435 mm	4000K - CRI>80	6683 Lm
2100LD4072EL	72	LD	1435 mm	4000K - CRI>80	9662 Lm

LED | CE | 220 V_~ 240 | -25°C +45°C | IP66 | IK08 | RG0 | CRI >80 | 3 step MacAdam
 <10% flicker | L90-B10 >60.000h | L80-B50 >100.000h | 7 YEARS WARRANTY

MIG 1

mod. T2



Code	W tot.	Mod.	Optic	°K - CRI	LUMEN OUTPUT
9200T24054GL	54	T2	Street	4000K - CRI>70	6630 Lm
9200T24080GL	80	T2	Street	4000K - CRI>70	9945 Lm

LED | CE | 220 V_~ 240 | -25°C +45°C | IP66 | IK08 | RG0 | CRI >70 | 3 step MacAdam
 <4% flicker FREE | L90-B10 >60.000h | L80-B50 >100.000h | 10 kV | RAL 9006 | 7 YEARS WARRANTY

MIG 2

mod. T2



Code	W tot.	Mod.	Optic	°K - CRI	LUMEN OUTPUT
9201T24120GL	120	T2	Street	4000K - CRI>70	14918 Lm

LED | CE | 220 V_~ 240 | -25°C +45°C | IP66 | IK08 | RG0 | CRI >70 | 3 step MacAdam
 <4% flicker FREE | L90-B10 >60.000h | L80-B50 >100.000h | 10 kV | RAL 9006 | 7 YEARS WARRANTY

LEILA HP

mod. QP

mod. RP



Code	W tot.	Mod.	Optic	°K - CRI	LUMEN OUTPUT
1807QP0431EL	31	QP	UGR <19	4000K - CRI>80	4105 Lm
1807RP0431EL	31	RP	UGR <19	4000K - CRI>80	4105 Lm

mod. QP = 595 x 595 x 10 mm
 mod. RP = 295 x 1195 x 10 mm

LED | CE | 220 V_~ 240 | -25°C +45°C | IP20 | IK07 | RG0 | CRI >80 | 3 step MacAdam
 <10% flicker | L90-B10 >50.000h | L80-B50 >90.000h | RAL 9003 | 7 YEARS WARRANTY

AURORA

mod. Q3

mod. R3



Code	W tot.	Mod.	Optic	°K - CRI	LUMEN OUTPUT
1881Q30432EL	32	Q3	UGR <19	4000K - CRI>80	3882 Lm
1881R30432EL	32	R3	UGR <19	4000K - CRI>80	3882 Lm

mod. Q3 = 595 x 595 x 60 mm
 mod. R3 = 295 x 1195 x 60 mm

LED | CE | 220 V_~ 240 | -25°C +45°C | IP40 | IK07 | RG0 | CRI >80 CRI >90 | 3 step MacAdam
 <3% flicker FREE | L90-B10 >60.000h | L80-B50 >100.000h | RAL 9003 | 7 YEARS WARRANTY

BLANCA

mod. RP



Code	W tot.	Mod.	Optic	°K - CRI	LUMEN OUTPUT
2011RP0433EL	33	RP	UGR <19	4000K - CRI>80	4261 Lm
2011RP0460EL	60	RP	UGR <19	4000K - CRI>80	7475 Lm

33W = 150 x 1250 x 35 mm
 60W = 150 x 1530 x 35 mm

LED | CE | 220 V_~ 240 | -25°C +45°C | IP40 | IK07 | RG0 | CRI >80 CRI >90 | 3 step MacAdam
 <3% flicker FREE | L90-B10 >60.000h | L80-B50 >100.000h | RAL 9003 | 7 YEARS WARRANTY